

CLEAR

CLEAR



Kwik Seal®

Adhesive Caulk



**Cured Caulk is
Mold & Mildew
Resistant**

- **Bonds Like a Glue,
Seals Like a Caulk**
- **Paintable**
- **Easy Water Clean-up
& Low Odor**

Kitchen, Bath & Plumbing



Read back panel for cautions!
¡Lea las precauciones en el panel posterior!

5.5 fl oz (162 mL)

DAP® KWIK SEAL® Kitchen & Bath Adhesive Caulk is an easy-to-use acrylic latex that bonds like a glue & seals like a caulk. Once cured, the caulk is mold & mildew resistant & 100% waterproof. Easy to apply, paintable, low in odor & cleans up with water.

FOR BEST RESULTS: Apply in temperatures above 40°F. Not for continuous underwater use. Joint width should not exceed 3/8". If joint depth exceeds 3/8", use a foam backer rod. Store away from extreme heat/cold. **Caulk applies white & dries clear in 7-14 days (depending on joint depth, temperatures, & humidity)**

INSTRUCTIONS: **1.** Surface must be clean, dry & free of old caulk & foreign material. **2.** Remove cap & cut nozzle at 45° angle to desired bead size. **3.** Squeeze caulk into gap or joint. **4.** Smooth bead. **5.** Clean up excess wet caulk with a damp sponge before it skins over. Clean hands & tools with warm water. Excess dried caulk must be cut or scraped away. **6. PAINTABLE.** Allow caulk to dry clear before painting with latex or oil-based paints. **7.** Wait at least 36 hours before exposing to water or moisture. **8.** Reseal tube for storage & reuse.

COVERAGE: 30 linear ft at 3/16" diameter bead

Caution! Contains ethylene glycol. May cause mild skin irritation. Do not get in eye, on skin, or on clothing. Use gloves and safety glasses. Use in well-ventilated area. Do not ingest. **In an emergency,** call poison control center at 800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit dap.com.

KEEP OUT OF REACH OF CHILDREN.

¡Precaución! Contiene etilenglicol. Puede causar una ligera irritación en la piel. Evite el contacto con los ojos, la piel y la ropa. Use guantes y gafas de seguridad. Utilice en un área con buena ventilación. No lo ingiere. **En caso de emergencia,** llame a un centro de control de envenenamiento al 800-222-1222. Para más información, consulte la Hoja de datos de seguridad (SDS). Para obtener un SDS, comuníquese con su proveedor o visite dap.com. **MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.**

⚠️WARNING Cancer and Reproductive Harm /

⚠️ADVERTENCIA Cáncer y Daños al Sistema Reproductor - www.P65warnings.ca.gov

NCCS Calif. ARB VOC
<1.5% wt/wt (45 g/L)



WARRANTY: If product fails to perform when used as directed, within one year of date of purchase, call **888-DAP-TIPS**, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be responsible for incidental or consequential damages.

QUESTIONS? ¿PREGUNTAS? Call/Llame al **888-DAP-TIPS** or visit/o visite dap.com & click on/ y pulse en "Ask the Expert."

Para obtener las instrucciones y garantía en español, llame al 888-327-8477 o visite dap.com.

DAP Products Inc.
Baltimore, MD 21224

Made in the USA with U.S. and globally sourced materials

dap.com