




RECTORSEAL[®]

PLUMBING PRODUCT CATALOG



Pipe Thread Sealants
Solvent Cements
Soldering Fluxes
DWV Solutions
Plumbing Products
Firestopping
Other Products



THANK YOU.



RectorSeal is proud to have been partnered with the trades through product development and innovation for over 75 years. Your continued trust and patronage of our products and services will never be taken for granted.

David M. Smith

President, RectorSeal Corporation

Catalog Contents & Product Features

RectorSeal® **Pipe Thread Sealants** are the finest thread sealants in the industry. Each batch of thread sealant is tested extensively for strict quality control to insure strong and reliable performance. This large selection of pipe thread sealants covers a variety of applications. **6-10**

RectorSeal® offers **Low-VOC Solvent Cements, Primers and Cleaners** in a variety of sizes for the building and construction trades. Use with PVC, ABS or CPVC pipes and fittings. You can rely on the high-quality, consistent performance of these products. **11-18**

Nokorode® **Soldering Fluxes** have been the brand preferred by contractors for over 100 years. Clean and flux in one operation. Save time and money. Fluxes are offered in lead-free, odorless, hot and cold weather, water washable and pre-tinning formulas that deliver a strong, leak-free joint. **19-22**

DWV Solutions Clean Check® backwater valves, HubSett™ test couplings and Magic Vent® air admittance valves. RectorSeal® offers a complete line of cost efficient solutions for DWV systems. **23-26**

Plumbing Products Calci-Free™ water heater flush, Leak locators, Lubricating oils, Cutting oils, Golden Tool Brand and other specialty tools. **27-34**

Metacaulk® **Firestopping** the worldwide leader in firestop technology. Specifically designed caulks and collars fill voids in construction joints and around penetrations in fire-rated walls or floors preventing the spread of fire. **35-44**

Other Products Kickstart® hard start devices, Acid Away® compressor burnout acid neutralizers, Anti-Seize compounds, Overflow switches, Speciality cleaners and degreasers. **45-57**

Index **58-59**



Scan for RectorSeal® homepage

Pipe Joining

Pipe Thread Sealants •

Low-VOC Solvent Cements •

Primers / Cleaners •

Paste Fluxes •

Soldering Accessories •



RECTORSEAL® PIPE THREAD SEALANTS



Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

RectorSeal No. 5®

Multi-purpose pipe thread sealant

Code	Description	Qty.
25790	1-¾ oz.	24
25631	¼ pt.	24
25551	½ pt.	24
25431	1 pt.	12
25300	1 qt.	12
25271	1 gal.	4
25191	5 gal.	1
25112	55 gal.	1

Application • Lubricates and protects threaded pipe and fittings • Can be pressurized immediately up to 100 psi for piping up to 2" diameter • Ideal for a wide variety of fluids and gases including potable water

Recommended for • Galvanized Steel • Iron • Brass • Copper • Aluminum • Stainless Steel • Polyethylene • RTRP • PVC



- FEATURES**
- Soft set / Slow drying
 - Lead free
 - Smooth application
 - 2 year shelf life
 - Certified to NSF/ANSI 61-G



Also available in 55 gal. container.

RectorSeal T plus 2®

PTFE enriched pipe thread sealant



Code	Description	Qty.
23710	1-¾ oz.	24
23631	¼ pt.	24
23551	½ pt.	24
23431	1 pt.	12
23391	1 qt.	12
23271	1 gal.	4
23191	5 gal.	1
23112	55 gal.	1

Application • Contains PTFE & synthetic fibers for superior performance • Can be pressurized immediately following application

Recommended for • Galvanized Steel • Iron
 • Brass • Copper
 • Aluminum • Stainless Steel
 • Polyethylene • RTRP
 • PVC • CPVC • ABS

Also available in 55 gal. container.



FEATURES

- Non-setting
- Lead free
- 2 year shelf life
- Certified to NSF/ANSI 61-G

RectorSeal Tru-Blu™

Vibration resistant pipe thread sealant



Code	Description	Qty.
31780	1-¾ oz.	24
31631	¼ pt.	24
31551	½ pt.	24
31431	1 pt.	12
31300	1 qt.	12

Application • For high vibration environments such as refrigeration and industrial applications • Designed for sealing vibration prone NPT connections

Recommended for • Galvanized Steel • Iron
 • Brass • Copper • Aluminum
 • Stainless Steel • PVC • Polyethylene
 • Reinforced fiberglass



FILE NO. 1282

FEATURES

- Fast drying / Flexible set
- Contains PTFE
- Lead free
- 2 year shelf life
- Certified to NSF/ANSI 61-G

*FBC™ System Compatible™ indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings.

**FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of the Lubrizol Corporation.

PIPE THREAD SEALANTS

Continued

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

No. 5[®] Special

Low odor pipe thread sealant

Code	Description	Qty.
26551	½ pt.	24
26431	1 pt.	12
26390	1 qt.	12
26271	1 gal.	4
26191	5 gal.	1
26112	55 gal.	1



FEATURES

- Low temperature application
- Non-hardening
- Lead free



Application • Non-staining, non-setting for use on gas piping or gas detection equipment • Can be pressurized immediately

Recommended for • Galvanized Steel

- Iron • Brass • Copper
- Aluminum • Stainless Steel
- Polyethylene • RTRP • PVC



See ordering chart for container sizes available.

No. 5[®] Sub-Zero

Low temperature, low odor pipe thread sealant

Code	Description	Qty.
27731	¼ pt.	24
27651	½ pt.	24
27541	1 pt.	12
27460	1 qt.	12
27371	1 gal.	4
27111	5 gal.	1
27222	55 gal.	1



FEATURES

- Low temperature application -35°F
- All weather formula
- Lead free



Application • Odorless, non-staining, low temperature application • Brushable to -35°F • Can be pressurized immediately

Recommended for • Galvanized Steel • Iron • Brass • Copper

- Aluminum • Stainless Steel
- Polyethylene • RTRP • PVC



See ordering chart for container sizes available.

No. 100 Virgin[™]

Industrial grade PTFE pipe thread sealant

Code	Description	Qty.
22631	¼ pt.	24
22551	½ pt.	24
22431	1 pt.	12
22390	1 qt.	12
22271	1 gal.	4
22191	5 gal.	1
22112	55 gal.	1



FEATURES

- Non-setting
- Lubricates & protects threads
- Lead free



Application • Non-hardening, industrial grade sealant containing virgin PTFE to provide maximum sealing performance

- Can be pressurized immediately
- Brushable from 20°F to 140°F

Recommended for

- Galvanized Steel • Iron
- Brass • Copper
- Aluminum • Stainless Steel
- Polyethylene • RTRP
- PVC • CPVC • ABS



See ordering chart for container sizes available.

No. 7 Corrosive chemical pipe thread sealant


Code	Description	Qty.
17432	1 pt.	4

- FEATURES**
- Soft Set
 - Lead free

Application • Slow drying sealant for use with lines carrying corrosive chemicals: diluted acids, caustics and other chemical solutions



- Recommended for**
- Galvanized Steel
 - Iron
 - Brass
 - Copper
 - Aluminum
 - Stainless Steel



No. 21 Black, slow dry/soft set pipe thread sealant

Code	Description	Qty.
28651	½ pt.	24
28541	1 pt.	12
28371	1 gal.	4
28111	5 gal.	1
28222	55 gal.	1



- FEATURES**
- Black sealant
 - Lead free
 - Multi-purpose



Application • Soft set sealant for lines carrying a wide range of liquids and gases • For applications where black color is preferred

- Brushable from 20°F to 140°F

- Recommended for**
- Galvanized Steel
 - Iron
 - Brass
 - Copper
 - Aluminum
 - Stainless Steel
 - Polyethylene
 - RTRP
 - PVC

Also available in 55 gal. container.

PTFE Tape 100% pure PTFE pipe thread sealant tape

Code	Description	Qty.
35942	½" x 260"	12
35943	½" x 520"	12
35944	½" x 1296"	12
35945	¾" x 260"	12
35946	¾" x 520"	12
35947	¾" x 1296"	12
35948	1" x 260"	12
35949	1" x 520"	12



Application • Resistant to most liquids and gases as it is completely inert

- Available in a wide variety of sizes.



GENERAL SERVICE RECOMMENDATIONS*

Pipe Thread Sealants

PIPE THREAD SEALANTS								
Material	No. 5®	T plus 2®	Tru-Blu™	No. 5® Special	No. 5® Sub-Zero	No. 100 Virgin™	No. 7	No. 21
Acids, dilute	●	●	●	●	●	●	●	●
Air, compressed	●	●	●	●	●	●	●	●
Alcohols							●	
Ammonia, gaseous	●	●	●	●	●	●	●	●
Aliphatic solvents	●	●	●	●	●		●	●
Aromatic solvents		●					●	
Caustic, dilute	●	●	●	●	●	●	●	●
Cutting oils (low aromatic)	●	●	●	●	●	●	●	●
Diesel fuel oil	●		●	●	●		●	●
Ethylene glycol (anti-freeze)							●	
Fatty acids, liquid							●	
Gasohol (unleaded & 10% alcohol)	●						●	●
Gasoline	●		●	●	●		●	●
Glycerine							●	
Heating oils	●	●	●	●	●	●	●	●
Helium, gaseous	●	●	●	●	●	●	●	●
Hydraulic oils	●	●	●	●	●	●	●	●
Hydraulic fluids (water/glycol type)							●	
Hydrogen, gaseous	●	●	●	●	●	●	●	●
Inert gases	●	●	●	●	●	●	●	●
Jet fuel (JP3, 4 & 5)	●		●	●	●		●	●
Kerosene	●		●	●	●		●	●
Liquefied petroleum gases	●	●					●	●
Mineral oils	●		●	●	●	●	●	●
Natural gas	●	●	●	●	●	●	●	●
Nitrogen, gaseous	●	●	●	●	●	●	●	●
Refrigerants			●					
Soap, liquid	●	●	●	●	●	●	●	●
Steam	●		●	●	●		●	●
Vegetable oils	●	●	●	●	●	●	●	●
Water (hot or cold)	●	●	●	●	●	●	●	●

*The above chart is only a guide for the selection of an appropriate thread sealant for use with broad classifications of applications. It is not a recommendation for a specific service application. Please contact our technical service department with details of your application for a recommendation for the appropriate thread sealant.



RECTORSEAL® LOW-VOC SOLVENT CEMENTS

Apply all solvent cements in conjunction with RectorSeal primer

Pete™ 602L

○ Clear - medium body PVC solvent cement

Code	Description	Qty.
55922	¼ pt.	24
55924	½ pt.	24
55926	1 pt.	12
55928	1 qt.	12
55916	1 gal.	4



pw-g-dwv-sw



FILE NO. 1796

FEATURES

- Reduces product run-off
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs

Application • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • For up to 6" for schedule 40; 1-¼" for schedule 80

Recommended for • Potable water
• Pressure pipe • Gas • Conduit
• Sewers • DWV systems



Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

LOW-VOC SOLVENT CEMENTS

Continued

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

Gene™ 404L

○ Clear - regular body PVC solvent cement

Code	Description	Qty.
55901	¼ pt.	24
55902	½ pt.	24
55904	1 pt.	12
55906	1 qt.	12
55908	1 gal.	4



PW-G-DWV-SW



FILE NO. 1796

FEATURES

- Fast setting formula
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 & D3138 specs

Application • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • ABS to PVC non-pressured transition joints • Schedule 40 up to 2" pressure; up to 4" non-pressure pipe (DWV)

Recommended for

- Potable water
- Pressure pipe • Gas
- Conduit • Sewers
- DWV systems



Gold™ 844L

○ Clear - heavy body PVC solvent cement

Code	Description	Qty.
55950	¼ pt.	24
55951	½ pt.	24
55952	1 pt.	12
55954	1 qt.	12
55955	1 gal.	4



PW-G-DWV-SW



FILE NO. 1796

FEATURES

- Excellent gap filling
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs

Application • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • For pipe up to 12" schedule 40 and schedule 80

Recommended for

- Potable water
- Pressure pipe • Gas
- Conduit • Sewers
- DWV systems



Homer™ 828L

○ Gray - heavy body PVC solvent cement



Code	Description	Qty.
55960	½ pt.	24
55961	1 pt.	12
55963	1 qt.	12
55964	1 gal.	4



PW-S-DWV-SW



FILE NO. 1796

FEATURES

- Superior bonding strength
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs

Application • Polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • For pipe up to 12" schedule 40 and

schedule 80

- Remains stable from 0°F to 120°F
- Recommended for**
- Potable water
 - Pressure pipe
 - Gas • Conduit
 - Sewers
 - DWV systems



Also available in gal. can

Arctic™ 616L

○ Clear - medium body PVC solvent cement

Code	Description	Qty.
55909	½ pt.	24
55919	1 pt.	12
55948	1 qt.	12
55953	1 gal.	4



PW-S-DWV-SW



FILE NO. 1796

FEATURES

- Formulated for use in cold weather
- LEED compliant
- NSF approved for potable water
- 2 year shelf life
- Exceeds ASTM D2564 specs

Application • Premium polyvinyl chloride (PVC) solvent cement used for joining PVC pipe and socket-type fittings which meet Class 12454 as defined in ASTM specification D1784 • Pipe up to 6" schedule 40; 1-¼" schedule 80 • Remains stable from 0°F to 120°F

Recommended for

- Potable water • Pressure pipe
- Gas • Conduit • Sewers
- DWV systems



Also available in gal. can

John™ 647L

● Black - medium body ABS solvent cement

Code	Description	Qty.
55938	¼ pt.	24
55940	½ pt.	24
55942	1 pt.	12
55944	1 qt.	12
55946	1 gal.	4



DWV-SW



FILE NO. 1796

FEATURES

- For ABS pipe
- LEED compliant
- 2 year shelf life
- Exceeds ASTM D2235 specs

Application • Used for joining Acrylonitrile butadiene styrene (ABS) pipe and socket-type fittings which meet classes as defined in ASTM specification D1788

- Pipe up to 6" on all schedules • Use year-round; remains stable from 0°F to 120°F

Recommended for

- ABS Pressure pipe
- Gas • Conduit
- Sewers
- DWV systems



Also available in gal. can

LOW-VOC SOLVENT CEMENTS

Continued

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

Charlie™ 412L

Orange - regular body CPVC solvent cement

Code	Description	Qty.
55956	¼ pt.	24
55957	½ pt.	24
55966	1 gal.	4



PW-G-009



FILE NO. 4586

FEATURES

- For CPVC pipe
- LEED compliant
- 2 year shelf life
- Meets ASTM F493 specs

Application • Chlorinated polyvinyl chloride (CPVC) solvent cement for joining CPVC pipe, tubing and socket-type fittings which meet Class 23497 as defined in ASTM specification D1784

- For use on CPVC pipe up to 2" schedule 40

Recommended for

- Potable water
- Pressure pipe
- Sewers
- DWV systems



Also available in gal. can

Heavy Duty 811L

Orange - heavy body CPVC solvent cement

Code	Description	Qty.
55967	1 pt.	12
55968	1 qt.	12
55971	1 gal.	4



PW-G-009-01



FILE NO. 4586

FEATURES

- For CPVC pipe
- LEED compliant
- 2 year shelf life
- Meets ASTM F493 specs

Application • Chlorinated polyvinyl chloride (CPVC) solvent cement for joining CPVC pipe, tubing and socket-type fittings which meet Class 23497 as defined in ASTM specification D1784

- For use on CPVC pipe up to 12" schedule 40 and schedule 80

Recommended for

- Potable water
- Pressure pipe
- Sewers
- DWV systems



Also available in gal. can

Mike™ 425L

Amber - regular body multi-purpose solvent cement

Code	Description	Qty.
55969	¼ pt.	24
55970	½ pt.	24
55973	1 pt.	12
55974	1 qt.	12
55976	1 gal.	4

FEATURES

- Multi-purpose
- LEED compliant
- 2 year shelf life
- Meets ASTM 3138 specs

Application • For use on PVC, CPVC and ABS plastic pipe and socket-type fittings • Can be used on transitions joints to join PVC to CPVC and PVC to ABS

Recommended for

- Water
- Conduit
- DWV systems



Also available in gal. can

LOW-VOC SPECIALTY SOLVENT CEMENTS

Dura-Gold™ 627L

● Gold - medium body CPVC solvent cement

Code	Description	Qty.
55992	½ pt.	24
55998	1 pt.	12



PG-DWV-001



FILE NO. 4586

FEATURES

- One-step, no primer needed
- LEED compliant
- 2 year shelf life
- Meets ASTM F493 specs

Application • Chlorinated polyvinyl chloride (CPVC) solvent cement used for joining FlowGuard Gold™ CPVC and fittings • All schedules and classes up to 2" schedule 40 and up to 1-¼" on schedule 80

Recommended for

- All CPVC pipe
- Potable water
- Pressure pipe
- DWV systems

*FlowGuard Gold is a licensed trademark of the Lubrizol Corporation



Hot™ 203L

● Blue - medium body PVC solvent cement

Code	Description	Qty.
55988	¼ pt.	24
55989	½ pt.	24
55990	1 pt.	12
55993	1 qt.	12
55994	1 gal.	4



PG-DWV-001



FILE NO. 1796

FEATURES

- Fast drying
- Excellent in cold weather
- LEED compliant
- 2 year shelf life
- Meets ASTM D2564 specs

Application • Polyvinyl chloride (PVC) solvent cement joins both rigid and flexible PVC pipe and socket-type fittings which meet Class 1245 as defined in ASTM specifications D1784 • For all rigid PVC classes up to 6" schedule 40 and 1-¼" schedule 80

Recommended for

- Irrigation • Pools
- Spas • Potable water
- Pressure pipe • Gas
- Conduit • Sewers
- DWV systems
- Flexible PVC hose



Also available in gal. can

PVC Electrical Conduit 633L

○ Clear/Gray - medium body solvent cement

Code	Description	Qty.
55980	½ pt. - clear	24
55983	1 pt. - clear	12
55985	1 qt. - clear	12
55986	1 gal. - clear	4
55995	1 pt. - gray	12
55996	1 qt. - gray	12



PG-DWV-001



FILE NO. 1796

Clear Only

FEATURES

- Conduit types I & II
- No primer needed on ENT
- LEED compliant
- 2 year shelf life
- Meets ASTM D2564 specs

Application • Clear or gray to match conduit color • Thick formula to reduce runoff • Up to and including 6" Schedule 40 and Schedule 80

Recommended for

- PVC conduit





RECTORSEAL® PRIMERS & CLEANERS

Jim™ PR-1L

○ Purple - Low-VOC hi-etch primer

Code	Description	Qty.
55910	¼ pt.	24
55912	½ pt.	24
55914	1 pt.	12
55918	1 qt.	12
55920	1 gal.	4

Application • Prepares surfaces for superior bonding strength • For use on PVC and CPVC pipe, tubing and socket-type fittings in both schedule 40 and schedule 80

Recommended for • Potable water
• Pressure pipe • Gas • Conduit
• Sewers • DWV systems



PW-G-DWV



FILE NO. 4585

FEATURES

- Fast acting
- Superior bonding
- LEED compliant
- 2 year shelf life
- Low-VOC
- Meets ASTM F656 specs



Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

Clear PR-2L

○ Clear - Low-VOC hi-etch primer

Code	Description	Qty.
55972	1 pt.	12
55981	1 qt.	12
55982	1 gal.	4



FEATURES

- Fast acting
- Superior bonding
- LEED compliant
- 2 year shelf life
- Low-VOC
- Meets ASTM F656 specs



Application

- Prepares surfaces for superior bonding strength
- For use on PVC and CPVC pipe, tubing and socket-type fittings in both schedule 40 and schedule 80

Recommended for

- Potable water
- Pressure pipe
- Gas
- Conduit
- Sewers
- DWV systems



Bill™ PR-3

○ Clear - Hi-etch primer

Code	Description	Qty.
55701	¼ pt.	24
55703	½ pt.	24
55705	1 pt.	12
55707	1 qt.	12
55709	1 gal.	4

FEATURES

- PVC & CPVC systems
- Etches & penetrates
- Safe for potable water
- 2 year shelf life



- Application**
- Primer for use on all PVC and CPVC pipe, tubing and socket-type fittings to etch and penetrate the surface increasing body strength
 - Use with all sizes and classes in both schedule 40 and schedule 80

Recommended for

- Potable water
- Pressure pipe
- Gas
- Conduit
- DWV systems

Sam™ CL-3L

○ Clear - Low-VOC cleaner

Code	Description	Qty.
55929	¼ pt.	24
55930	½ pt.	24
55932	1 pt.	12
55934	1 qt.	12
55936	1 gal.	4



FEATURES

- Fast acting
- Safe for potable water
- LEED compliant
- 2 year shelf life
- Low-VOC

- Application**
- Clear cleaner for dissolving grease and dirt to prepare bonding surfaces for solvent cementing
 - Use for PVC, CPVC and ABS pipe, tubing and socket-type fittings schedule 40 and schedule 80

- Recommended for**
- Potable water
 - Pressure pipe
 - Gas
 - Conduit
 - DWV systems



GENERAL SERVICE RECOMMENDATIONS

Solvent Cements • Cleaners • Primers

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

SOLVENT CEMENTS						
Product Name	Pete 602L	Gene 404L	Gold 844L	Homer 828L	Arctic 616L	John 647L
Application	PVC	PVC & Transition Joints	PVC	PVC	PVC	PVC
Color	Clear	Clear	Clear	Gray	Gray	Black
Max. Pipe Size Schedule 40	6"	2" Pressure	12"	12"	6"	6"
Max. Pipe Size Schedule 80	1¼"	4" DWV	12"	12"	1¼"	6"
Body Type	Medium Body	Regular Body	Heavy Body	Heavy Body	Medium Body	Medium Body
Cure Time	Fast Set	Fast Set	Medium Set	Medium Set	Fast Set	Medium Set
ASTM	D2564	D2564, D3138	D2564	D2564	D2564	D2235

SOLVENT CEMENTS						
Product Name	Charlie 412L	Heavy Duty 811L	Mike 425L	Dura-Gold 627L	Hot 203L	PVC Electrical Conduit 633L
Application	CPVC	CPVC	Multipurpose ABS/PVC/CPVC	CPVC	PVC	PVC
Color	Orange	Orange	Amber	Gold	Blue	Gray / Clear
Max. Pipe Size Schedule 40	2"	12"	2" Pressure	2"	6"	6"
Max. Pipe Size Schedule 80	—	12"	6" DWV	2"	1¼"	6"
Body Type	Regular Body	Heavy Body	Regular Body	Medium Body	Medium Body	Medium Body
Cure Time	Fast Set	Medium Set	Fast Set	Medium Set	Very Fast Set	Fast Set
ASTM	F493	F493	D3138	F493	D2564	D2564

CLEANERS & PRIMERS				
Product Name	Sam CL-3L	Jim PR-1L	Clear PR-2L	Bill PR-3
Product Type	Cleaner	Primer	Primer	Primer
Application	PVC, CPVC, ABS	PVC, CPVC	PVC, CPVC	PVC, CPVC
Color	Clear	Purple	Clear	Clear



NOKORODE® PASTE FLUXES

Nokorode® Aqua Flux™

Code	Description	Qty.
74044	2 oz.	48
74047	4 oz.	24
74046	16 oz.	12



FEATURES

- Lead free
- Creamy, smooth paste
- Safe for potable water systems
- Certified to NSF/ANSI 61-G
- Meets ASTM B-813 specs
- Complies with AB 1953 requirements

Water washable flux

Application

- Meets the ASTM B-813 standard requiring that flux residue shall be water flushable after soldering
- Superior wetting ability; Allows solder to flow easily and uniformly into joints
- Lead free joints

Recommended for

- Solid wire solders 95/5, 60/40, 50/50 and 40/60
- For use with the silicon family of metal alloy products



NOKORODE® PASTE FLUXES

Continued

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

Nokorode® Regular

Multi-purpose paste flux

Code	Description	Qty.
14000	1.7 oz.	48
14010	4 oz.	24
14020	8 oz. tool box	24
14030	1 lb.	12



FEATURES

- Lead Free
- Cleans & fluxes all at one time
- Safe for potable water systems
- Certified to NSF/ANSI 61-G
- Meets O-F-506 Type 1A & A-A-51145, MIL-F-4995-2 specs

Application • All purpose, soft soldering paste flux with a special oil base that protects the solder against corrosive attack

- Non-aggressive formula. Ideal for copper and brass fittings

Recommended for

- All solder alloys including 95/5 and lead free solders



Nokorode® Hot Weather

Does not liquefy in hot temperatures

Code	Description	Qty.
14800	1.7 oz.	48
14820	8 oz. tool box	24
14830	1 lb.	12

FEATURES

- Lead Free
- Cleans & fluxes all at one time
- Meets O-F-506 Type 1A & A-A-51145, MIL-F-4995-2 specs

Application • Formulated to remain firm and stable in higher temperatures • Non-aggressive formula for use on copper and brass fittings

Recommended for

- All solder alloys including 95/5 and lead free solders



Nokorode® Cold Weather

Does not harden in cold temperatures

Code	Description	Qty.
14700	1.7 oz.	48
14720	8 oz.	24
14730	1 lb.	12

FEATURES

- Lead Free
- Cleans & fluxes all at one time
- Meets O-F-506 Type 1A & A-A-51145, MIL-F-4995-2 specs

Application • Formulated to stay soft and sticky in cold weather • Low corrosivity, scorching and spattering. Works to deliver a strong, leak-free joint

Recommended for

- All solder alloys including 95/5 and lead free solders



SPECIALTY FLUXES

Nokorode® Pre-Tinning

Code	Description	Qty.
14115	8 oz. tool box	24


FEATURES

- Lead free
- Cleans, pre-tins and fluxes
- Excellent wetting ability

95/5 Paste Flux

Application • Formulated with 95/5 tin/antimony which pre-tins before wire solder is applied • Excellent for use on large diameter fittings or faster soldering of smaller diameter fittings

Recommended for • 95/5 • 50/50
• Common metals (copper, tin, zinc, nickel and sheet lead)



C-Flux®

High quality flux

Code	Description	Qty.
74026	3 oz.	48
74025	12 oz.	24

FEATURES

- Lead free
- Blend of 95/5 tin/antimony

Application • Soft soldering, multi-purpose paste that contains a blend of flux and powdered solder (95/5 tin/antimony) • Cleans, fluxes and pretins in one operation

Recommended for
• 95/5 • 60/40 • 50/50 • 40/60
• All solderable metals (copper, tin, zinc, nickel and sheet lead)



Amos Feer's Famous Flux™

Premium grade flux

Code	Description	Qty.
75590	8 oz.	24

FEATURES

- Lead free
- Flows smoothly
- Excellent pre-tinning characteristics

Application • Multi-purpose paste-type flux containing a blend of flux and powdered 95/5 tin • Cleans contact area, fluxes and pretins in one operation
• Won't become runny and separate at temperatures up to 120°F

Recommended for • 95/5 • 60/40
• 50/50 • 40/60 • All solderable metals (copper, tin, zinc, nickel and sheet lead)



Fluxomatic™ Gel

Instant acting flux

Code	Description	Qty.
74104	8 oz.	24

FEATURES

- Non-acid
- No fumes or odor
- Leaves no residue
- Will not clog valves

Application • Prepares metals for rapid soldering in the 370°F to 550°F range • Easy application assures total removal of oxide films and a joint that is completely soldered

Recommended for • Copper • Brass • Bronze
• Tin • Zinc • Sheet metal • Stainless steel
• Galvanized metal • Nickel • Chrome • Monel
• Ferrous metal (cast iron, iron and steel)



Rectorshield™

Heat absorption paste

Code	Description	Qty.
83554	11 oz. tube	24

FEATURES

- Biodegradable
- Odorless

Application • A heat absorption paste to help prevent damage to sensitive controls, valves, plastic faucet parts, equipment and other soldered connections • Reduces heat transfer by absorbing thermal energy from heat and flames

Recommended for

- Copper
- Other types of metal pipe



Regular Sandcloth

Standard abrasion

Code	Description	Qty.
61720	10 yd.	50
61730	25 yd.	20

FEATURES

- Sharp, aluminum-oxide quality sandcloth
- Strong, flexible cloth backing

Application • Ideal for the preparation of copper tubing and fittings where water and solvents are not a major factor

Recommended for

- Copper



Open Mesh Sandcloth

Reusable waterproof abrasion

Code	Description	Qty.
61760	5 yd.	50
61759	10 yd.	50
61758	25 yd.	20

FEATURES


- Reuseable
- 100% waterproof
- Tear-resistant nylon backing

Application • A premium abrasive, waterproof material with top quality performance

- If the material becomes loaded with fillings, simply rinse in water and tap out.

Recommended for

- Copper



DWV Solutions

Backwater Valves •

Test Couplings •

Air Admittance Valves •

Trap Fittings •





DWV SOLUTIONS

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

Clean Check®

Extendable Backwater Valve Kit

Code	Description	Qty.
96903	3" ABS	6
96904	4" ABS	6
96913	3" ABS w/adaptor & plug	4
96914	4" ABS w/adaptor & plug	4
96923	3" PVC	6
96924	4" PVC	6
96926	6" PVC	3
96933	3" PVC w/adaptor & plug	4
96934	4" PVC w/adaptor & plug	4



FEATURES

- No manhole required
- Installs up to 12 ft. below ground level
- Above ground maintenance accessibility
- 75 PSI rated flapper
- Meets IPC & UPC IAPMO plumbing codes

Application • Prevents sewage backup into a residence or commercial building as a result of a plugged sewer system, excess volume in the system or groundwater flooding

Recommended for • PVC • ABS

Kit Includes • Tee-shaped valve body • Top collar • Bottom collar w/ replaceable 75 PSI flapper



Ground level access.
(cap not included)

Can install to a depth
up to 12 ft. below
ground level.
(pipe length not included)

Flap assembly lifts up
out of hole for easy
flapper replacement



Kit available in both ABS & PVC



US Patent No. 5,234,018

Hubsett™

Test coupling

Code	Description	Qty.
97050	3" ABS w/ hub & spigot	12
97051	3" PVC w/ hub & spigot	12
97052	4" ABS	12
97053	4" PVC	12
97063	4" PVC w/ hub & spigot	12



FEATURES

- Holds pressure every time
- Safe to use
- No pump or special tools needed
- Test with air or water
- 12 ft. cord

Application • Uniquely designed coupling and test device all-in-one
 • Allows the building's drain waste and vent system to be connected to the sewer line prior to the initial test
 • Easily removed with one quick pull on the release cord

Recommended for • ABS • PVC
Includes • Dome • Coupling • Float



Tom-Kap™

Flush-fit cleanout adapter & plug

Code	Description	Qty.
97480	2" ABS	24
97481	2" PVC	24
97482	3" ABS	24
97483	3" PVC	24
97484	4" ABS	24
97485	4" PVC	24

FEATURES

- Reduces installation cost
- Simplifies rough-in

Application • Threaded adapter cements inside the pipe, providing a flush-finished cleanout for DWV systems

Recommended for
 • Schedule 40 • SDR-35 • Foam core
Includes • Top fitting • Cap



DWV SOLUTIONS

Continued

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

Magic Vent®

Air admittance valves

Code	Description	Qty.
97400	Micro	12
97405	Micro w/ PVC adapter	12
97406	Micro w/ ABS adapter	12



FEATURES

- Eliminates roof penetrations
- Great design flexibility
- Saves time and money
- Permitted for use in accordance with: IPC 2012, Sec 917; IRC 2012; Manufactured Housing Construction and Safety Standard 2001

Application • Performs the function of a DWV system vent stack, protecting the trap seal from siphonage without the need for additional piping to the outdoors

Recommended for

- PVC
- ABS



US Patent No. D427,286

Magic Trap™

Tubular polypropylene fitting


Code	Description	Qty.
97402	Trap with threaded tee	12

FEATURES

- Automatically places AAV 4" above drain pipes
- Saves time & money
- Tee threads directly into AAV

Application • 1-1/2" fitting replaces any standard 1-1/2" tubular trap

- Magic Vent® Micro threads directly onto the tee connection of the Magic Trap™



Plumbing Products

Water Heater Flush •

Specialty Tools •

Leak Locators •

Lubricant & Cutting Oils •

Root Destroyer •



PLUMBING PRODUCTS



Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

Calci-Free™

Tankless water heater flush

Code	Description	Qty.
68708	1.2 lbs.	12



FEATURES

- Restores circulation in 20 min.
- More effective than vinegar
- Easy to use with no strong odor
- Cleans heat exchanger fast
- Biodegradable

Application • Economical cleaner that restores circulation and pressure in commercial and residential tankless water heaters • Cleans heater coils thoroughly

Recommended for • Routine cleaning to remove calcium and other solid deposits from heating coils in tankless water heaters



Calci-Free™ Kit

Complete tankless water heater flush kit

Code	Description	Qty.
68711	Flush kit	1

FEATURES

- A complete cleaning system
- Cleans in only 20 minutes
- Easy to use
- Heavy duty, chemical resistant utility pump

Application • The complete system to clean & restore efficiency to tankless water heaters • Includes everything needed to safely and effectively remove scale and mineral deposits

Recommended for • Routine cleaning to remove calcium and other solid deposits from heating coils in tankless water heaters



Frugal Flush®

Adjustable flapper valve

Code	Description	Qty.
97760	Retroflapper™	12
97771	Universal 1.6 Blistercard	12
97774	Universal 1.6 Master carton	144

FEATURES

- Early closing flapper
- Superior performance
- Adjustable dial

Application • Water conservation device
 • Adjustable dial allows for water savings

Recommended for • Retroflapper™ reduces water consumption in 3.5, 5 and 7 gal. tanks • Universal 1.6 replacement flapper is for 1.6 gal. tanks

U.S. Patent No. 5,390,375



Quick Saw™

Cable saw

Code	Description	Qty.
97575	Cable Saw	12

FEATURES

- Economical, durable
- Contoured, detachable handles
- 24" cable

Application • Ideal for cutting buried PVC pipe • Pipe located between joists
 • Cutting PVC pipe flush with walls or floors



Pipe Repair Kit

Quick-fix pipe repair system

Code	Description	Qty.
82112	Pipe repair kit	12

FEATURES

- Easy to use
- Fast setting, durable repair
- Reduces repair cost
- Withstands pressure up to 450 PSI

Application • Stops leaks on all rigid pipes
 • Consists of a 2" x 4' knitted fiberglass cloth coated with a water-activated polyurethane resin that adheres to all metal, plastic, fiberglass and concrete piping

Recommended for

- Plumbing • Pool • Spa • Irrigation
- HVAC applications



Water Heater Stand

Pre-assembled stand

Code	Description	Qty.
97750	For 30, 40 & 50 gal.	6
97753	For 75 & 100 gal.	3

FEATURES

- Compliance with National Fire Protection Association
- 2 sizes available

Application • One piece stand made of 3/4" square carbon-steel tubing
 • Each stand carries a live load test of 2000 lbs.





GoldenGrip® Internal pipe wrench

Code	Description	Qty.
97250	Single ½"	6
97251	Single ¾"	6
97252	Double 1" - 1¼"	3
97253	Double 1½" - 2"	3
97256	Set of 4 tools	1

FEATURES

- Self-locking & reversible
- No thread damage
- Works in tight spaces

Application • The right tool for quick and easy installation or extraction of pipe nipples • Self-locking, reversible internal wrench can be used with ratchets, extensions and impact wrenches

Recommended for • Chrome Pipe
• Brass pipe • Can also be used to extract corroded pipe



Sold separately in four sizes or as a set of four with durable carry case



U.S. Patent No. 6,675,679B2

Golden Pipe Shredder™

Code	Description	Qty.
98040	1-½"	4
98041	2"	4
98042	3"	4
98043	4"	4
98050	Set of 4 tools	1

FEATURES

- Carbide cutting blades
- Unique guiding system
- Made of heat tempered steel
- One piece body

Restore welded plastic fittings

Application • Reams out solvent welded plastic fittings so they can be reused • Cuts stub outs to be flush or recessed with wall • Removes cracked water closet flanges



Sold separately in four sizes or as a set of four with durable carry case

Golden Extractor™

Tub drain tool

Code	Description	Qty.
97258	Universal	3

FEATURES

- Quickly extracts tub drains
- Use to install new tub drains
- Built in bolt/screw remover
- Universal size
- Made of heat tempered steel

Application • For extracting tub drains
 • Utilizes a standard 3/8" drive ratchet to remove tub drains even when the cross arms are broken
 • Installs new drains
 • Removes bolts/screws where the heads are broken off or just won't move



U.S. Patent No. 7,024,972

LEAK LOCATORS



Better Bubble™

Gas leak locator

Code	Description	Qty.
65554	8 oz. - dauber top	12
65432	32 oz. - trigger spray	12
65273	1 gal.	4

Application • Thick formula pinpoints the smallest natural gas, LPG and A/C refrigerant leaks with well defined elastic bubbles that stand up under pressure and windy conditions • Use on surface temperatures from 20°F to 250°F

Recommended for • All types of pipe, tubing, valves, tanks, pressure vessels, condenser / evaporator coils, refrigeration coils, and many other similar applications



FEATURES

- Fast acting
- Long lasting
- Easy to see bubbles
- Continuous bubbling



*FBC™ System Compatible™ indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings.

**FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of the Lubrizol Corporation.

RectorSeek™ Low-Temp

Code	Description	Qty.
61554	8 oz. dauber top	12
61434	16 oz. trigger spray	12
61273	1 gal.	4
61158	5 gal.	1
61111	55 gal.	1

FEATURES

- Longer bubbling action
- Dauber or spray application
- Easy to apply

Low temperature leak locator

Application • Leak locator for use on pipes or tanks containing gases at low temperatures • Effective from -35°F to 200°F

Recommended for • All types of pipe, tubing, valves, cylinders, tanks, pressure vessels, condenser / evaporator coils, refrigeration coils and many other similar applications



RectorSeek™ Mid-Temp

Code	Description	Qty.
60554	8 oz. dauber top	12
60434	16 oz. trigger spray	12
60273	1 gal.	4
60158	5 gal.	1
60111	55 gal.	1

FEATURES

- Longer bubbling action
- Dauber or spray application
- Easy to apply

Normal temperature leak locator

Application • Leak locator for use at normal temperature on pipe or tanks that contain gases • Can be used on oxygen, air or gas at temperatures between 40°F to 200°F

Recommended for

• All types of pipe, tubing, valves, cylinders, tanks, pressure vessels, condenser / evaporator coils, refrigeration coils and many other similar applications



PLUMBING PRODUCTS

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

Pipe Lube

Lubricant for gasketed pipe

Code	Description	Qty.
97700	2 lbs.	12



FEATURES

- Contains no petroleum
- Non-toxic & biodegradable

Application • Lubricant for use on all types of gasketed pipe
 • Can be used on potable water systems



Dark Cutting Oil

Low rpm machine thread cutting oil

Code	Description	Qty.
94392	1 qt.	12
94272	1 gal.	6
94192	5 gal.	1
94111	55 gal.	1

FEATURES

- Increased lubricity/longer die life
- Penetrates quickly
- Keeps dies cool.

Application • Designed to reduce friction
 • Effective coolant and anti-weld agent
 • An extreme pressure lubricant during thread cutting operations
 • Will not congeal above 20°F



Light Cutting Oil

High rpm machine thread cutting oil

Code	Description	Qty.
93392	1 qt.	12
93272	1 gal.	6
93192	5 gal.	1
93111	55 gal.	1

FEATURES

- Increased lubricity/longer die life
- Penetrates quickly
- Keeps dies cool.

Application • Designed to reduce friction
 • Effective coolant and anti-weld agent
 • An extreme pressure lubricant during thread cutting operations
 • Will not congeal above 20°F



Root Destroyer

Destroy root growth

Code	Description	Qty.
81394	2 lbs.	12
81559	50 lbs.	1

FEATURES

- Fast acting at dissolving roots
- Will not harm tree or shrub
- Meets EPA Reg. No. 1278-5-5

Application • Formulated to destroy and control the growth of roots which enter sewer systems through the pipe joints or cracks
 • Absorbed only by the roots



Firestopping

Intumescent Sealants •

Elastomeric Sealants •

Pipe Collars and Sleeves •

Putty Sticks and Pads •

Joint Strips •

Electrical Products •



METACAULK® FIRESTOP SEALANTS



Metacaulk® 1000

Intumescent, water-based firestop sealant

Code	Description	Qty.
66640	10.3 oz. cartridge	12
66303	30 oz. cartridge	12
66312	20.2 oz. sausage pack	12
66305	1 gal.	4
66307	2 gal.	1
66309	5 gal.	1

Application • Will prevent the spread of fire through joint openings and through-penetrations
 • No dilution or mixing required • Can be used in areas under constant vibration and movement
 • Use in fire-rated gypsum wallboard partitions, concrete walls or floors, wood floors and concrete or corrugated steel deck floor/ceiling assemblies

Recommended for • Metal • Insulated
 • Fiberglass & plastic pipes • Wall construction joints • Power & telephone cables



FEATURES

- UL Classified systems up to 4 hrs
- Highly intumescent
- Excellent freeze-thaw
- For interior use - paintable
- VOC compliant
- STC rating 62
- Meets ASTM E 814, UL 1479 & UL 2079 standards



See ordering chart for container sizes available.

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

*FBC™ System Compatible™ indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold™, BlazeMaster™ and Corzan™ pipe and fittings.

**FBC™, FlowGuard Gold™, BlazeMaster™ and Corzan™ are licensed trademarks of the Lubrizol Corporation.

Metacaulk® MC 150+

General purpose firestop sealant

Code	Description	Qty.
66648	10.3 oz. cartridge	12
66383	30 oz. cartridge	12
66385	20.2 oz. sausage pack	12
66389	5 gal.	1



FEATURES

- Water-based - VOC compliant
- STC rating 51
- Excellent freeze-thaw
- Use for most common applications

Application • One component, general purpose fire-rated sealant and smoke seal for construction joints and through-penetrations on both horizontal and vertical surfaces

- Non-sag caulking grade sealant that is easy to apply as well as to retrofit
- Can be used in areas under constant vibration or movement

Recommended for

- Metal
- Insulated
- Fiberglass and plastic pipes
- Wall construction joints
- Power and telephone cables



Metacaulk® 350i

Elastomeric seal firestop sealant

Code	Description	Qty.
66616	10.3 oz. cartridge	12
66611	20.2 oz. sausage pack	12
66613	5 gal.	1



FEATURES

- Sound rated
- Excellent freeze-thaw
- STC rating 53

Application • One component, general purpose sealant and smoke seal

- Intumescent, water-based, non-sag caulking grade sealant that is easy to apply and great for retrofits
- Suitable for dynamic movement

Recommended for

- Metal
- Insulated
- Fiberglass & plastic pipes
- Wall construction joints
- Power & telephone cables



Metacaulk® 835+

Elastomeric, Silicone firestop sealant

Code	Description	Qty.
66645	10.15 oz. cartridge	12
66019	5 gal.	1



FEATURES

- Exterior / Interior use
- Water resistant
- STC rating 55

Application • Used in systems where dynamic movement is expected

- Resistant to chemical exposure

Recommended for • PVC pipe on closed (pressure) systems

- EMT
- Insulated and uninsulated steel pipe
- Construction and control joints
- Interior expansion joints

Also available in
5 gal. pail



METACAULK® FIRESTOP SEALANTS

Continued

Metacaulk® 1200

Sprayable firestop mastic

Code	Description	Qty.
66015	30 oz. cartridge - red	12
66292	20.2 oz. sausage pk - red	12
66521	1 qt. self leveling - red	12
66379	5 gal. spray - red	1
66387	5 gal. caulk grade - red	1
66523	5 gal. self leveling - red	1
66525	30 oz. cartridge - white	12
66527	5 gal. spray - white	1

Application • Excellent fire-rated acoustical sealant, cures to an elastomeric seal suitable for dynamic movement
 • Available in 3 consistencies: spray allows fast, economical installation on long joint runs, self leveling is made for horizontal application and caulk grade is a non-sag sealant

Recommended for • Construction joints such as: top of the wall, curtain wall perimeter, expansion, control and etc. • Cable trays



Sprayable 5 gal. container
 also available - red & white



FEATURES

- Sprayable, brushable & trowelable
- Flexible - elastomeric
- Excellent smoke seal
- Excellent freeze-thaw
- VOC compliant
- STC rating 50



*FBC™ System Compatible™ indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings.

**FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of the Lubrizol Corporation.

PREFABRICATED FIRESTOP DEVICES

Metacaulk® Pipe Collars

Code	Description	Qty.
66352	1-1/2"	12
66353	2"	12
66350	3"	6
66351	4"	6
66354	6"	2



FEATURES

- No measurements of material
- Fits in limited access areas
- 25% reduction of installation time

Prefabricated firestop system



Application • UL classified for both open and closed pipe systems • Simple locking mechanism for easy installation

Recommended for • PVC • CPVC • ABS
 • PVC foam core • ABS foam core • FRPP
 • PEX pipe • Electrical cable



U.S. Patent No. 6,207,085

Metacaulk® Intumescent Sleeve

Firestop seal

Code	Description	Qty.
66584	For 2", 3" & 4" Pipe	6
66582	For 6" & 8" Pipe	1




FEATURES

- No steel bolts or fasteners
- Can be retrofitted
- Flexible

Application • Firestop through penetrations with a single sleeve • Ideal for combustible pipes penetrating a concrete fluted deck assembly

Recommended for • PVC • cc-PVC
 • CPVC • FRPP • PP • ABS • PP-R
 • Rigid non-metallic conduit installations



- Thread Sealants
- Solvent Cements
- Fluxes
- DWV Solutions
- Plumbing Products
- Firestopping
- Other Products

METACAULK® FIRESTOP PRODUCTS

Continued

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

Putty Sticks & Pads

Code	Description	Qty.
66345	18 cu./in. - stick	12
66340	6" x 7" x 1/8" thick	20
66335	7" x 7" x 1/8" thick	20



FEATURES

- Applied by hand
- No asbestos fillers
- Pads - STC rating 60
- For interior use
- Adheres to all common building surfaces

Fire-rated putty

Application • Putty sticks are used to seal around penetrating items through fire-rated walls, floors and within blank openings

- Putty pads are used to maintain the hourly rating of fire-rated walls containing electrical outlet boxes and to reduce sound transmission
- Hand moldable with no curing time



Box Guard™

Fire-rated pad for electrical boxes

Code	Description	Qty.
66366	Single box	50
66367	Double box	50
66369	4-11/16" x 4-11/16"	50



FEATURES

- Adheres to back of electrical box
- Non-conductive
- Highly intumescent
- STC rating 53

Application • One component fire-rated for use in electrical boxes • It is inserted on the inside back wall of an electrical box prior to wiring



US Patent No. 6,207,085 & 6,252,167

Cover Guard™

Fire-rated gasket for electrical boxes

Code	Description	Qty.
66270	Double receptacle	50
66272	Single receptacle	50
66274	Double switch	50
66276	Single switch	50
66265	Single decor	50
66266	Double decor	50



FEATURES

- Reduces sound transmission
- Easy to install
- Highly intumescent
- STC rating 54

Application • A single component fire-rated gasket for use with electrical boxes to comply with the "24 inch rule" • Fits under the cover plate and does not take up volume



US Patent No. 6,207,085; 6,252,167 & 7,348,484

Firestop Pillows

For large temporary openings

Code	Description	Qty.
66362	2" x 9" x 6"	10
66363	3" x 9" x 6"	10



FEATURES

- Forms a very strong char
- No wire mesh required
- Easy to install - no tools

Application • Intumescent • Designed for use primarily in large temporary or frequently accessed openings with cables, cable trays, blank openings or multiple penetrations



Fire-Rated Mortar

For large openings

Code	Description	Qty.
66331	20 lbs. pail	1
66334	45 lbs. bag	1



FEATURES

- Non-sag adjustable consistency
- High yield per lb.
- No special tools needed

Application • Rapid hardening gypsum/cement compound for large openings
 • Sets without shrinking and can form a rigid, gas tight, fire resistant seal
 • Can be cut or drilled and resealed

Recommended for

- Power cables • Fiber optic
- Telephone cables • Aluminium or steel cable trays • EMT
- Copper • Steel • Cast iron pipe



Composite Sheet

For large openings with penetrating items

Code	Description	Qty.
66320	36" x 36"	1



FEATURES

- Light weight
- Thinner sheets
- Re-enterable
- No VOC

Application • Rigid fire resistive panel used to seal penetrations and restore the fire rating to floor/ceilings or walls • Made of reinforced, highly intumescent material bonded on one side to a galvanized steel sheet
 • Ideal for clean room applications



US Patent No. 6,207,085

METACAULK® FIRESTOP PRODUCTS

Continued

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

Joint Strip

Flexible material for up to 1" wide joints

Code	Description	Qty.
66700	1/16" x 1" x 82' strip	6
66701	1/16" x 1-1/2" x 82' strip	4
66704	1/16" x 2" x 82' strip	3
66702	1/16" x 2-1/2" x 82' strip	2
66703	1/16" x 3" x 82' strip	2



FEATURES

- No firestop caulk required
- Single sided application
- Simple & easy to use

Application • Flexible strip firestop material used in concrete and masonry floor and wall joints up to 1" wide • Prevents the passage of fire between joints

Recommended for

- Stadium construction, tilt up panels
- Curtain wall panels
- All concrete and masonry wall and floor construction joint applications

US Patent No. 6,207,085



Wrap Strip

Flexible intumescent strip for plastic and insulated pipe

Code	Description	Qty.
66135	1" x 12'	6
66136	2" x 12'	4



FEATURES

- No cure time
- Easy to apply
- Long length means less waste
- Systems up to 14" PVC
- Highly intumescent

Application • Simply wrap required number of strips around penetrating item to completely fill the annular space or as required by system design

- When exposed to heat, expands to form a hard char to seal off the penetration

Recommended for

- Plastic and insulated pipe applications

US Patent No. 6,207,085



Industrial Cable Coating

For power cables

Code	Description	Qty.
50250	5 gal.	1



FEATURES

- No cable derating
- Interior & exterior use

Application • Water-based heavy duty spray coating designed to prevent vertical and horizontal spread of fire along grouped or single communication or power cables

- Compatible with and adheres to typical cable jacketing materials



*FBC™ System Compatible™ indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings.

**FBC®, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of the Lubrizol Corporation.

Sound Transmission Class (STC) rating - Tested in a UL 411 wall assembly/section to ASTM E90

FIRESTOP ACCESSORIES

Caulking Guns Cartridge, sausage & bulk loading

Code	Description	Qty.
66114	10.3 oz. gun	1
66115	30 oz. gun	1
66116	20.2 oz. sausage gun	1
66117	Replacement tips	25
66093	24 oz. bulk loading gun	1

- FEATURES**
- Industrial grade



Universal Collar For concrete, wood & gypsum

Code	Description	Qty.
66091	2" x 50' roll	1
66095	1" x 50' roll	1

- FEATURES**
- Galvanized steel



Foam Backer Rod Fills gaps prior to sealing

Code	Description	Qty.
66112	1" x 75'	1

- FEATURES**
- Easy to use
 - Economical



6lb./ cu. ft. Safing Mineral wool backing

Code	Description	Qty.
66101	2" thick	8

- FEATURES**
- Non-combustible backing



Wire Mesh Screen Underlayment

Code	Description	Qty.
66106	4-3/4" x 100' roll	1

- FEATURES**
- Galvanized steel mesh



Delta Deck Plugs 36" long

Code	Description	Qty.
66401	1-1/2" x 3-1/2" x 4-1/2"	48
66403	1-1/2" x 4-1/2" x 5-1/2"	39
66409	3" x 5" x 7"	18

- FEATURES**
- Non-combustible
 - Mineral wool backing for fluted deck



Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

METACAULK® APPLICATION CHART

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

PIPE APPLICATION												
Application	1000	MC 150+	350i	835+	1200	Mortar	Putty	Putty Pads	Wrap Strip	Joint Strip	Pipe Collar	Intumescent Sleeve
Metal Pipe - EMT, Copper	●	●	●	●		●	●					
Multiple Metal	●		●	●		●						
Insulated Metal Pipe	●		●	●					●			
Open Plastic Pipe - 2" & smaller	●		●						●		●	●
Open Plastic Pipe - up to 4"									●		●	●
Closed Plastic Pipe - 4" & smaller	●								●		●	●
Open/Closed Plastic Pipe - 6"											●	●
Open/Closed Plastic Pipe - 8"												●
Glass Pipe				●								

CABLE APPLICATION									
Application	1000	MC 150+	350i	835+	1200	Mortar	Putty	Pillows	Composite Sheet
Single or Bundled Cables	●	●	●	●		●	●		
Cable Trays					●	●		●	●

CONSTRUCTION APPLICATION								
Application	1000	835+	1200	Joint Strip	Mortar	Pillows	Putty	Composite Sheet
Construction Joints	●	●	●	●				
Top of Wall	●	●	●	●				
Large Openings					●	●		●
Blank Openings					●	●	●	●

ELECTRICAL APPLICATION			
Application	Box Guard™		Putty Pads
Electrical Outlet Boxes	●	●	●

Other Products

- Potential Relay and Start Capacitors
- Acid Neutralizers
- Anti-Seize Compounds
- Condensate Overflow Switches
- Specialty Sealant Caulks
- Specialty Cleaners



HVAC PRODUCTS



Kickstart®

Potential relay & start capacitor

Code	Description	Qty.
96506	KS-1	20
96503	TO-5	20




FEATURES

- 2-wire design for easy installation
- 2-year warranty
- Extend the life of compressors
- OEM tested & approved

Application • 2-wired starting device that uses a mechanical potential relay & start capacitor • Assist compressors in starting under very adverse conditions such as low voltage or high head pressures extending the life of compressors by bringing them up to full speed more quickly and efficiently

Recommended for • Single phase 208V, 230V, and 265V A/C, refrigeration and heat pump compressors • KS-1 handles 3.5 - 5.0 ton maximum torque • TO-5 handles 1.0 - 3.0 ton maximum torque



Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

Acid Away®

Compressor burnout acid neutralizer

Code	Description	Qty.
45004	4 oz.	12

FEATURES

- Stays active in the system
- Preventive maintenance
- Safe for system components
- Tested to ANSI/ASHRAE standards 86-1983 & 97-1989

Application • Chemical treatment for A/C and refrigeration systems that have experienced a burnout or operating systems that are showing a buildup in acid content • No clogging or damage to line-sets from by-products of acid neutralization

Recommended for • Both hermetic or semi-hermetic compressors that operate with standard CFC or HCFC refrigerants using mineral oil or alkybenzene type refrigeration oils



U. S. Patent No. 5,503,757

Acid Away® for POE

Acid neutralizer for POE oils

Code	Description	Qty.
45009	4 oz.	12

FEATURES

- Removes residual acid
- Compatible with Polyol Ester lubricants
- Preventative maintenance
- Tested to ANSI/ASHRAE standards 86-1983 & 97-1989

Application • Prevents compressor burnouts by removing the acid buildup that occurs in Polyol Ester refrigeration oils used in A/C and refrigeration systems.

Recommended for • Both hermetic or semi-hermetic compressors that operate with Polyol Ester lubricants



US Patent No. 5,503,757

ANTI-SEIZE COMPOUNDS

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

Break-Out™

High temperature anti-seize

Code	Description	Qty.
73551	8 oz.	12
73861	12 oz. aerosol	12
73431	1 lb.	12
73271	9.6 lbs.	4
73361	48 lbs.	1

FEATURES

- Will not wash off
- Stainless steel up to 550°F
- Contains no lead
- Exceeds military spec MIL-A-907E

Application • Fine copper flakes and graphite particles dispersed in a high temperature, corrosion resistant grease for use on bolts, nuts and screws

- Resists seizure for easy breakout up to 1800°F
- Color: bronze

Recommended for

- Stainless steel up to 550°F



Food Grade

Food Contact anti-seize and lubricant

Code	Description	Qty.
73931	1 lb.	12

FEATURES

- Food Grade
- Use with potable water
- Conforms to FDA regulations CFR-21-178, 3570

Application • Specifically for use when incidental food contact is possible • PTFE for added lubricity

- Prevents rust, corrosion, seizing and galling of metal compounds
- Color: white

Recommended for

- Service rating -65°F to 1800°F



Copper-Rich™

High temperature anti-seize and lubricant

Code	Description	Qty.
72851	8 oz.	12
72841	1 lb.	12

FEATURES

- Highly conductive
- Exceeds military spec MIL-A-907E

Application • Pure micro-sized copper flakes dispersed in a non-melt, high temperature grease • Resists seizure
• Color: copper

Recommended for

- All metal connections including stainless steel to 1800°F
- Ideal for use where electrical conductivity is important



Nickel-Rich™

Nuclear grade high temperature anti-seize and lubricant

Code	Description	Qty.
73851	8 oz.	12
73831	1 lb.	12

FEATURES

- Will not wash off
- Brushable down to 0°F
- Exceeds military spec MIL-A-907E

Application • Pure nickel flakes dispersed in a high temperature, corrosion resistant grease
• Resists attack by acidic and caustic chemicals • Color: silver

Recommended for

- Stainless steel up to 2600°F



Moly-Rich™

High temperature corrosion resistant anti-seize and lubricant

Code	Description	Qty.
71431	1 lb.	12

FEATURES

- Will not wash off
- Not affected by vibration
- Exceeds military spec MIL-A-907E
- Low coefficient of friction allows easy breakout up to 1050°F

Application • Fine Molybdenum disulfide, graphite particles and extreme pressure additives dispersed in a high temperature, corrosion resistant grease • Color: blue

Recommended for

- Stainless steel up to 500°F





SAFE-T-SWITCH® CONDENSATE OVERFLOW SWITCHES

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

Model SS1

Primary drains or auxiliary drain outlets

Code	Description	Qty.
97632	Model SS1	24



FEATURES

- Condensate overflow switch
- Magnetic reed switch
- Install vertically or horizontally
- Connect to either red or yellow wire



Application • Detects clogged A/C condensate drains and shuts off the system to prevent water damage to floors, walls and ceilings • Can be installed horizontally or vertically, inline or on the primary pan's auxiliary drain outlet by using the included 3/4" adapter, bushing and cap • Can be installed on a sloping line and does not need to be level or plumb

US Patent No. 6,442,955



Model SS2


Primary pan auxiliary outlet

Code	Description	Qty.
97637	Model SS2	24



FEATURES

- Condensate overflow switch
- Magnetic reed switch
- Connect to either red or yellow wire



Application • Detects clogged A/C condensate drains and shuts off the system • Using the 3/4" adapter the SS2 can be installed on the auxiliary outlet of the primary drain pan • Easy access to the switch and the primary drain line for service

US Patent No. 6,442,955



Model SS3


Primary & auxiliary drain pans

Code	Description	Qty.
97647	Model SS3	24



FEATURES

- Condensate overflow switch
- Magnetic reed switch
- Connect to either red or yellow wire



Application • Detects clogged A/C condensate drains and shuts off the system • Steel mounting bracket clips firmly over the edge of most drain pans • Slim-profile can be installed on primary or auxiliary drain pans

US Patent No. 6,698,215



Model SS4

Drain pans w/ slanted sides or lipped edges

Code	Description	Qty.
97625	Model SS4	24



FEATURES

- Condensate overflow switch
- Magnetic reed switch
- Connect to either red or yellow wire

Application • Detects clogged A/C condensate drains and shuts off the system • Adjustable clip to fit over slanted sides and lipped edges of primary and auxiliary drain pans



Model SS3-CT

Systems with communicating thermostats

Code	Description	Qty.
97652	Model SS3-CT	24



FEATURES

- Condensate overflow switch
- Magnetic reed switch
- Connect to either red or yellow wire

Application • Detects clogged A/C condensate drains • Normally open condensate overflow switch can be connected to the accessory wires of the communicating thermostat • Installed on primary or auxiliary drain pans



US Patent No. 6,698,215

Model SS2AP

Plenum rated

Code	Description	Qty.
97640	Model SS2AP	50



FEATURES

- Condensate overflow switch
- Magnetic reed switch
- Connect to either red or yellow wire

Application • Detects clogged A/C condensate drains and shuts off the system • Schedule 80 CPVC, plenum rated and listed to UL-2043 • Use 3/4" adapter to install on the auxiliary outlet of the primary drain pan



US Patent No. 6,442,955

Model SG1

Condensate overflow alarm

Code	Description	Qty.
97655	Model SG1	50



FEATURES

- 2-wire design
- Works with 24V overflow switches

Application • Sounds a buzzer and flashes an LED when an overflow switch or condensate pump cuts the thermostat circuit



US Patent No. 7,199,722

SAFE-T-SWITCH® ELECTRONIC PROBE SENSORS

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

SS 103 E

Dual sensors

Code	Description	Qty.
97692	SS 103 E	24



FEATURES

- Electronic probe sensor
- Simple 2-wire design
- Onboard LED indicator
- Connect to either red or yellow wire



Application

- For primary drain line and auxiliary drain pan or auxiliary drain outlet and auxiliary drain pan
- Can be installed horizontally or vertically or inline
- Onboard LED indicates the condition of the unit at a glance
- No moving parts



SS 500 EP

Commercial rooftop downflow units

Code	Description	Qty.
97693	SS 500 EP	12



FEATURES

- Electronic probe sensor
- Simple 2-wire design
- Onboard LED indicator
- Plenum rated wire
- Connect to either red or yellow wire



- Application**
- Install on primary drain pan when plenum rating is needed
 - Small size and slim profile great for use on commercial rooftop downflow units



SS 700 E

Directly in the secondary drain pan

Code	Description	Qty.
97695	SS 700 E	12



FEATURES

- Works in any position
- Universal puck works in all secondary drain pans
- Onboard LED indicator



- Application**
- Designed to sit directly in a secondary drain pan, eliminating screws and clips
 - Multiple position option for the sensor and provides adjustable heights
 - Great for use in plastic overflow pans with round edges

SS 610 E

Mini split systems

Code	Description	Qty.
97622	SS 610 E	12



FEATURES

- Sensor connects to indoor units
- Attaches to pan or coils with unique bracket
- Onboard LED indicator can be mounted to side of unit
- No batteries required



- Application**
- Designed for mini split systems
 - For installation directly on primary drain pan or clipped to coils above primary drain pan
 - Multi-voltage
 - Can be wired in both normally open & normally closed systems

RectorSeal® RS 136

Fire block / smoke seal caulk

Code	Description	Qty.
66408	10.3 oz. cartridge	12



FEATURES

- Easy application
- Interior applications
- Water Clean-up

Application • General purpose, residential acoustical fireblock

Recommended for

- Electrical • Plumbing • Plastic pipe • Telephone communication systems penetrations



RectorSeal® Silicone Sealant

General purpose

Code	Description	Qty.
57505	10.3 oz. tube - white	12
57506	10.3 oz. tube - clear	12

FEATURES

- Remains flexible
- Vibration resistant
- Indoors/outdoor

Application • Ideal for general sealing

- Dry to touch in 30 minutes and fully cures in 24 hours

Recommended for

- Around electrical panels • Windows • Doors
- Pipes/vents • Corner joints • Aluminum siding
- Other interior/exterior building materials



RectorSeal® Hi-Temp™

100% RTV silicone caulk

Code	Description	Qty.
57500	10.1 oz. cartridge	24

FEATURES

- One component
- USDA specs for use in federally inspected meat and poultry plants
- F.D.A. reg #21 CFR 177.2600
- TT-S-001543A (COM-NBS) Class A
- TT-S00230C (COM-NBS) Class AA
- MIL-A-46106B Amend 3, Type 1
- Canadian 19-GP-9MA, Type 1

Application • Cures to a strong durable resilient rubber

Recommended for • Glass • Clean metal • Most types of non-oily wood • Vulcanized silicone rubber • Silicone resins • Natural and synthetic fiber • Ceramic • Paper • Many painted and plastic surfaces



Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

SPECIALTY CLEANERS

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

K.O. Dirt Blaster™

Dirt and grease stripper

Code	Description	Qty.
88438	20 oz. aerosol	12

FEATURES

- Dissolves grease quickly
- Quick drying
- Pressure washes small condenser coils without a water rinse
- Non-flammable
- No CFC's



Application

- Quickly dissolves grease
- Non-conductive so will not short out electrical equipment
- Effective on restaurant grease and other greasy surfaces

Recommended for

- Refrigeration coils
- Oil burner surfaces
- Machine parts
- Switches
- Relays
- Circuit breakers
- Motors
- Electrical components

Clean-N-Safe™

Condenser & evaporator coil cleaner

Code	Description	Qty.
83780	20 oz. aerosol	12

FEATURES

- Deep cleaning foam
- Non-acid
- Reduces energy cost
- Environmentally friendly
- Biodegradable



Application

- Effectively cleans and removes soils
- Foam powers off dirt and build-up without chemically attacking (corrode) coils, surrounding metal, other HVAC equipment components or adjacent roofing materials

Recommended for

- Air conditioning
- Refrigeration
- Heat pump coils

Zipp™

Quick drying degreaser

Code	Description	Qty.
82642	14 oz. aerosol	12

FEATURES

- Cleaner / degreaser
- Leaves no residue
- Non-flammable
- Non-conductive

Application • Quick drying, safety solvent degreaser that instantly removes grease, oil, waxes, tar, gums, grime, dirt, carbon, greasy stains, bilge slime and similar soils from most hard surfaces • Will not short out electrical equipment

Recommended for use • Oil burner parts
• Compressors • Refrigeration units
• Greasy fan blades • Strainers • Engines
• Stoves • Relay contact points
• Electrical equipment

**Zipp™ II**

Environmentally safer, quick drying degreaser

Code	Description	Qty.
82645	12 oz. aerosol	12

FEATURES

- Cleaner / degreaser
- Leaves no residue
- Non-flammable
- Non-conductive
- Non-chlorinated

Application • Quick drying, safety solvent degreaser that instantly removes grease, oil, waxes, tar, gums, grime, dirt, carbon, greasy stains, bilge slime and similar soils from most hard surfaces • Will not short out electrical equipment • Contains no carbon tet or restricted solvents

Recommended for use • Oil burner parts
• Compressors • Refrigeration units
• Greasy fan blades • Strainers • Engines
• Stoves • Relay contact points
• Electrical equipment

**Grime-Solv™**

Foaming, heavy duty cleaner and degreaser

Code	Description	Qty.
88436	14 oz. aerosol	12

FEATURES

- Safe for metals
- Wipes clean or rinses with water
- Non-flammable
- Non-corrosive

Application • Lifts encrusted grime, grease or carbon • Use to remove stains from concrete driveways and brick walls, to clean white wall tires and for cleaning surfaces before painting

Recommended for • Oil burning • A/C and refrigeration equipment • Marine and automotive engines • Machinery that can be rinsed with water or wiped with a rag



MISCELLANEOUS

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

Draft-Block™

Expanding polyurethane foam

Code	Description	Qty.
96500	12 oz. aerosol	12

FEATURES

- Expands 3X
- Tack-free in approx. 45 min.
- No ureaformaldehyde

Application • Excellent filler which bonds and insulates • Fill voids, cracks, crevices and small cavities on flat or irregular surfaces • Reduces sound transmission • Totally dielectric



Lets-Go™

Penetrant, lubricant and freeze-up preventer

Code	Description	Qty.
73012	12 oz. aerosol	12

FEATURES

- Loosens frozen bolts, nuts & joints
- Protects from water & weather

Application • Covers metal surfaces with a clinging, tough, long-lasting film of lubricant • The wetting power acts quickly on rusted and seized parts • Displaces moisture from wiring and equipment.



Cold Galvanizing Spray

Protection of hot-dip galvanizing

Code	Description	Qty.
86625	16 oz. aerosol	12

FEATURES

- Stops rust and corrosion
- Indoors or outdoors

Application • Contains 95% pure zinc and forms a tough, durable and flexible zinc metal coating that bonds electrochemically with the base metal to protect against rust and corrosion • To prevent and retard rust and corrosion on welded joints, fencing, storage tanks, pipe lines, metal buildings, marine and other similar applications



RectorSeal® EP-200

Code	Description	Qty.
97600	2 oz.	24
97601	2 oz. refill	24
97602	Blistercard	12
97606	EP-400 4 oz.	12



- FEATURES**
- Mixes like putty
 - Hardens in minutes
 - Can be drilled, taped, filed, machined, sanded and painted
 - Bonds and fills a variety of materials

Epoxy putty

Application • Pre-measured, high-grade epoxy and hardener formulated together in one stick
 • Break off the amount needed for each repair • Bonds to most surfaces



GOJO®*

Hand cleaner

Code	Description	Qty.
40500	Original 14 oz. tub	12
40507	Natural orange 14 oz.	12

- FEATURES**
- Safe to use
 - Non-toxic
 - Biodegradable

Application • Thoroughly and safely cleans adhesives, asphalt, tar and paint

*GOJO is a registered trademark of GOJO Industries



Buz-Awf™

Wasp and hornet spray

Code	Description	Qty.
84390	16 oz. aerosol	12

- FEATURES**
- High pressure spray
 - Shoots 20 ft stream
 - Non-conductive up to 47KV

Application • Kills wasps, hornets, yellow jackets and bees • E.P.A. REG. NO. 3862-174-51219, E.P.A. EST. NO. 9143-TX-1



PRODUCT INDEX

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products

- # -
 95/5 Pre-tinning Paste Flux 21

- A -
 Acid-Away 47
 Acid-Away for POE..... 47
 Air Admittance Valve 26
 Amos Feer's 21
 Aqua Flux 19
 Arctic 13

- B -
 Backwater Valve 24
 Better Bubble 32
 Bill 17
 Box Guard 40
 Breakout 48
 Buz-Awf 57

- C -
 C-Flux 21
 Calci-Free 28
 Calci-Free Kit 28
 Caulk 53
 Charlie 14
 Clean Check 24
 Clean-N-Safe 54
 Clear 17
 Coil Cleaner 54
 Cold Galvanizing 56
 Cold Weather 20
 Composite Sheet 41
 Compressor Hard Start Device 46
 Condensate Overflow Control Switch 50
 Copper-Rich 49
 Cover Guard 40
 Cutting Oil 34

- D -
 Draft-Block 56
 Dura-Gold 15

- E -
 Electrical Conduit Cement 15
 Epoxy Putty 57

- F -
 Fire Rated Mortar 41
 Firestop Caulk 36
 Flux 19
 Fluxomatic 21
 Food Grade Anti-Seize 48
 Frugal Flush 29

- G -
 Gene 12
 Go-Jo 57
 Gold 12
 Golden Extractor 31
 Golden Pipe Shredder 31
 GoldenGrip 30
 Grime-Solv 55

- H -
 Heavy Duty 14
 Hi-Temp 53
 Homer 13
 Hot 15
 Hot Weather 20
 Hubsett 25

- I -
 Intumescent Sleeve 39

- J -
 Jim 16
 John 13
 Joint Strip 42

- K -
 Kickstart 46
 KO Dirt Blaster 54

- L -
 Lets-Go 56
 Low-Voc Solvent Cement 11

- M -
 Magic Vent 26
 Magic Trap 26
 Metacaulk 1000 36
 Metacaulk 1200 38
 Metacaulk 350i 37
 Metacaulk 835+ 37
 Metacaulk Cable Coating 42
 Metacaulk MC 150+ 37
 Mike 14
 Moly-Rich 49

- N -
 Nickel-Rich 49
 No. 100 Virgin 8
 No. 21 9
 No. 5 6
 No. 5 Special 8
 No. 5 Sub-Zero 8
 No. 7 9
 Nokorode 20

- P -
 Pete 11
 Pillows 41
 Pipe Collars 39
 Pipe Lube 34
 Pipe Repair Kit 29
 PTFE Tape 9
 Putty Pads 40
 Putty Sticks 40
 PVC Electrical Conduit 15

- Q -
 Quick Saw 29

- R -
 RectorSeek Low-Temp 33
 RectorSeek Mid-Temp 33
 RectorShield 22
 Regular Paste 20
 Root Destroyer 34
 RS 136 53

- S -
 Safe-T-Gard 51
 Safe-T-Switch 50
 Sam 17
 Sandcloth 22
 Silicone Sealant 53
 Solvent Cement 11

- T -
 T Plus 2 7
 Tom Kap 25
 Tru-Blu 7
 Thread Sealant 6

- W -
 Water Heater Stand 29
 Wrap Strip 42

- Z -
 Zipp 55
 Zipp II 55

PRODUCT CODE INDEX

CODE	PAGE												
14000	20	28111	9	55934	17	60111	33	66340	40	73831	49	97251	30
14010	20	28222	9	55936	17	60158	33	66345	40	73851	49	97252	30
14020	20	28371	9	55938	13	60273	33	66350	39	73861	48	97253	30
14030	20	28541	9	55940	13	60434	33	66351	39	73931	48	97256	30
14115	21	28651	9	55942	13	60554	33	66352	39	74025	21	97258	31
14700	20	31300	7	55944	13	61111	33	66353	39	74026	21	97400	26
14720	20	31431	7	55946	13	61158	33	66354	39	74044	19	97402	26
14730	20	31551	7	55948	13	61273	33	66362	41	74046	19	97405	26
14800	20	31631	7	55950	12	61434	33	66363	41	74047	19	97406	26
14820	20	31780	7	55951	12	61554	33	66366	40	74104	21	97480	25
14830	20	35942	9	55952	12	61720	22	66367	40	75590	21	97481	25
17432	9	35943	9	55953	13	61730	22	66369	40	81394	34	97482	25
22112	8	35944	9	55954	12	61758	22	66379	38	81559	34	97483	25
22191	8	35945	9	55955	12	61759	22	66383	37	82112	29	97484	25
22271	8	35946	9	55956	14	61760	22	66385	37	82642	55	97485	25
22390	8	35947	9	55957	14	65273	32	66387	38	82645	55	97575	29
22431	8	35948	9	55960	13	65432	32	66389	37	83554	22	97600	57
22551	8	35949	9	55961	13	65554	32	66401	43	83780	54	97601	57
22631	8	40500	57	55963	13	66015	38	66403	43	84390	57	97602	57
23112	7	40507	57	55964	13	66019	37	66408	53	86625	56	97606	57
23191	7	45004	47	55966	14	66091	43	66409	43	88436	55	97622	52
23271	7	45009	47	55967	14	66093	43	66521	38	88438	54	97625	51
23391	7	50250	42	55968	14	66095	43	66523	38	93111	34	97632	50
23431	7	55701	17	55969	14	66101	43	66525	38	93192	34	97637	50
23551	7	55703	17	55970	14	66106	43	66527	38	93272	34	97640	51
23631	7	55705	17	55971	14	66112	43	66582	39	93392	34	97647	50
23710	7	55707	17	55972	17	66114	43	66584	39	94111	34	97652	51
25112	6	55709	17	55973	14	66115	43	66611	37	94192	34	97655	51
25191	6	55901	12	55974	14	66116	43	66613	37	94272	34	97692	52
25271	6	55902	12	55976	14	66117	43	66616	37	94392	34	97693	52
25300	6	55904	12	55980	15	66135	42	66640	36	96500	56	97695	52
25431	6	55906	12	55981	17	66136	42	66645	37	96503	46	97700	34
25551	6	55908	12	55982	17	66265	40	66648	37	96506	46	97750	29
25631	6	55909	13	55983	15	66266	40	66700	42	96903	24	97753	29
25790	6	55910	16	55985	15	66270	40	66701	42	96904	24	97760	29
26112	8	55912	16	55986	15	66272	40	66702	42	96913	24	97771	29
26191	8	55914	16	55988	15	66274	40	66703	42	96914	24	97774	29
26271	8	55916	11	55989	15	66276	40	66704	42	96923	24	98040	31
26390	8	55918	16	55990	15	66292	38	68708	28	96924	24	98041	31
26431	8	55919	13	55992	15	66303	36	68711	28	96926	24	98042	31
26551	8	55920	16	55993	15	66305	36	71431	49	96933	24	98043	31
27111	8	55922	11	55994	15	66307	36	72841	49	96934	24	98050	31
27222	8	55924	11	55995	15	66309	36	72851	49	97050	25		
27371	8	55926	11	55996	15	66312	36	73012	56	97051	25		
27460	8	55928	11	55998	15	66320	41	73271	48	97052	25		
27541	8	55929	17	57500	53	66331	41	73361	48	97053	25		
27651	8	55930	17	57505	53	66334	40	73431	48	97063	25		
27731	8	55932	17	57506	53	66335	41	73551	48	97250	30		

Thread Sealants

Solvent Cements

Fluxes

DWV Solutions

Plumbing Products

Firestopping

Other Products



Through the use of current technology and social media, RectorSeal provides up-to-date technical information and marketing materials.

Company Homepage:

An online hub of readily available resources for our full-line of specialty chemicals and tools including: product codes, MSDS and product data sheets. Promotional literature and artwork can be easily viewed. Trade show scheduling and booth information are also updated frequently.

Social Media:

Up to the minute information from RectorSeal regarding new products, press releases, market trends and trade articles are sent directly to your wall, time-line and mobile devices.

Online Video:

Watch instructional videos on how to effectively and properly use RectorSeal products. Subscribe to our channel and receive new product videos instantly.

Online Training:

Earn certifications from RectorSeal for approved field use of our specialty products. Lessons and exams can be completed at your own pace and results accessed from your personal computer.



To utilize these services, visit www.rectorseal.com

Contact: RectorSeal®

2601 Spenwick Drive, Houston, TX 77055

P 713-263-8001 | 800-231-3345

F 713-263-7577 | 800-441-0051

W www.rectorseal.com

Distributed by: